

# CIRCLE FLAMER

## X-F1800

- \ Fluid driven flamer system with 210° swiveling angles
- \ Up to 88 preset firing sequences
- \ Nozzle front design, safer for operator
- \ Safety lock with switchable test mode
- \ Stainless steel nozzle, reliable and durable
- \ Double electromagnetic valves design for additional safety
- \ Double pump ensure stable pressure
- \ Fitted with igniter signal interface, compatible with fireworks firing system
- \ Neutrik® powerCON TRUE1 in/out, Neutrik® 3-pin & 5-pin DMX in/out
- \ Compatible with SHOWVEN original host controller



### SPECIFICATIONS

- \ MODEL: X-F1800
- \ DIMENSION: 590×360×370mm
- \ WEIGHT: 30kg
- \ VOLTAGE: 100-240V, 50/60Hz
- \ POWER: 380W
- \ CONTROL: DMX
- \ INTERFACE: Neutrik® powerCON TRUE1 IN/OUT  
Neutrik® 3-pin & 5-pin XLR IN/OUT  
9V-60V Fireworks igniter signal port
- \ FLAME HEIGHT: up to 8-10m (no wind)
- \ ROTATE ANGLES: 210°(±105°)
- \ FUEL: ISOPAR-G, H, L, M; ISOPROPANOL, BIOETHANOL
- \ FUEL TANK CAPACITY: 10L
- \ FUEL CONSUMPTION RATE: 60ml/s
- \ EXT. BATTERY POWERED: YES

# CIRCLE FLAMER

## X-F3600

- \ Original innovation introduced by SHOWVEN
- \ Never seen flame effects up to 3 rotation cycles
- \ Full cycle and half cycle mode switchable
- \ Up to 182 preset firing sequences
- \ Nozzle front design, safer for operator
- \ Stainless steel nozzle, reliable and durable
- \ Safety lock with switchable test mode
- \ Double electromagnetic valves design for additional safety
- \ Double pump ensure stable pressure
- \ Fitted with igniter signal interface, compatible with fireworks firing system
- \ Neutrik<sup>®</sup> powerCON TRUE1 in/out, Neutrik<sup>®</sup> 3-pin & 5-pin DMX in/out



### SPECIFICATIONS

- \ MODEL: X-F3600
- \ ROTATION MODE: FULL CIRCLE MODE/HALF CIRCLE MODE
- \ DIMENSION: 640x360x370mm
- \ WEIGHT: 30kg
- \ VOLTAGE: 100-240V, 50/60Hz
- \ POWER: 380W
- \ CONTROL: DMX
- \ INTERFACE: Neutrik<sup>®</sup> powerCON TRUE1 IN/OUT  
Neutrik<sup>®</sup> 3-pin & 5-pin XLR IN/OUT  
9V-60V Fireworks igniter signal port
- \ FLAME HEIGHT: up to 8-10m (no wind)
- \ ROTATE ANGLES: 1080° (up to 3 cycles)
- \ FUEL: ISOPAR-G, H, L, M, ISOPROPANOL, BIOETHANOL
- \ FUEL TANK CAPACITY: 10L
- \ FUEL CONSUMPTION RATE: 60ml/s
- \ EXT. BATTERY POWERED: YES







