

U-FLAMER™

- \ Fluid driven vertical flamer original designed by SHOWVEN
- \ Flame up to 8-10m, indoor nozzle optional for flame up to 5-7m
- \ Super compact pumping system design, easy carrying
- \ Stainless steel housing, IPX3 waterproof design, reliable and durable
- \ Built-in 5L fuel tank, no external hose connection needed
- \ Double electromagnetic valves design for additional safety
- \ Safety lock with switchable test mode, safer for service
- \ Tilt protection, the tilt sensor will be activated when machine slant Over 45°
- \ Intelligent control system, safer for use
- \ Standard DMX control, compatible with all DMX console
- \ Neutrik® powerCON TRUE1 connectors
- \ Built-in battery, support 10min continuous firing or 2 to 3 days standby
- \ Built-in wireless control with radio range up to 1km



SPECIFICATIONS

- \ Model: U-FLAMER™
- \ DIMENSION: 280x260x320mm
- \ WEIGHT: 14kg
- \ CASING MATERIAL: 304 stainless steel
- \ VOLTAGE: 100-240V, 50/60Hz
- \ POWER: 300W
- \ CONTROL: DMX/Radio (1km)
- \ INTERFACE: Waterproof 3-pin XLR IN/OUT
- \ FLAME HEIGHT: Nozzle L 5-7m/Nozzle M 8-10m
- \ FUEL: ISOPROPANEL, ISOPAR-G,H,L,M
- \ FUEL TANK CAPACITY: 5L
- \ FUEL CONSUMPTION RATE: Nozzle L 60ml/s / Nozzle M 30ml/s
- \ EFFECT DIRECTION: Vertical
- \ IGNITION: High voltage electron ignition
- \ BUILT-IN BATTERY: YES
- \ WATERPROOF LEVEL: IPX3

