

## LOW FOG GENERATOR

### Creeper AQ

- \ Water based, no need of dry ice
- \ Molded enclosure, lighter, durable as well as rustless
- \ 30 heads atomizers, thicker fog output
- \ Weather proof design
- \ Abrasion-resistant silent caster
- \ Latest rapid heating technology, 1-2min heating up time
- \ Advanced auto water refill system
- \ Low-water sensor
- \ Adjustable fog density, moisture and fan speed, versatile application to meet different requirements
- \ Patented fog leakage prevention technology, no fog leakage even refill the machine when it is working

#### SPECIFICATIONS

- \ MODEL: Creeper AQ
- \ DIMENSION: 805x390x480mm
- \ WEIGHT: 35kg
- \ VOLTAGE: 100-120V/200-240V,50/60Hz
- \ POWER: 2000W
- \ HEAT UP TIME: 1-2min
- \ MAX FOG OUTPUT: 15000cuft/min
- \ FOG FLUID TANK CAPACITY: 3.3L
- \ MAX. FLUID CONSUMPTION: Appr.32ml/min
- \ WATER TANK CAPACITY: 24L
- \ MAX. WATER CONSUMPTION: Appr.375ml/min
- \ FULLY LOADED OUTPUT TIME: 100+ min
- \ INTERFACE: 3-PIN & 5-PIN XLR
- \ CONTROL: DMX 2/3 channel; Remote control
- \ CONSUMABLES: FX-M fog fluid, Water





## LOW FOG GENERATOR

### Creepers AQ PLUS

- \ Water based, no need of dry ice
- \ Molded enclosure, lighter, durable as well as rustless
- \ 40 heads atomizers, thicker fog output
- \ Weather proof design
- \ Abrasion-resistant silent caster
- \ Latest rapid heating technology, 1-2min heating up time
- \ Advanced auto water refill system
- \ Low-water sensor
- \ Adjustable fog density, moisture and fan speed, versatile application to meet different requirements
- \ Patented fog leakage prevention technology, no fog leakage even refill the machine when it is working

#### SPECIFICATIONS

- \ MODEL: Creeper AQ PLUS
- \ DIMENSION: 950x500x540mm
- \ WEIGHT: 48kg
- \ VOLTAGE: 100-120V/200-240V,50/60Hz
- \ POWER: 2500W
- \ HEAT UP TIME: 1-2min
- \ MAX FOG OUTPUT: 20000cuft/min
- \ FOG FLUID TANK CAPACITY: 3.3L
- \ MAX. FLUID CONSUMPTION: Appr.32ml/min
- \ WATER TANK CAPACITY: 35L
- \ MAX. WATER CONSUMPTION: Appr.500ml/min
- \ FULLY LOADED OUTPUT TIME: 100+ min
- \ INTERFACE: 3-PIN & 5-PIN XLR
- \ CONTROL: DMX 2/3 channel; Remote control
- \ CONSUMABLES: FX-M fog fluid, Water

